

Perfection Redefine.

PANTIN® Multipurpose Series **Electric Interchangeable Cooker**

ELECTRIC APPLIANCES





PANTIN® Multipurpose Series

Electric Interchangeable Cooker


Interchangeable Configuration





Digital Timer control

Digital temperature control with auto lift noodle basket to ensure accurate cooking time control.



Digital Timer control

Digital temperature control with auto lift noodle basket to ensure accurate cooking time control.




Simple Operate

Cut off power supply in case water drop below level to protect heating element and the user.



Interchangeable Configuration

Increase your productivity of having able to interchange the main body with different accessories to fulfill different cooking needs.



Pantin® Multipurpose Series Electric Interchangeable Cooker

Technical Specification

MODEL	COOKING TANK		DIMENSION (IN)			LIEDTZ	VOLTAGE	WATTACE
	HOLE	TANK	w	D	Н	HERTZ	VOLTAGE	WATTAGE
PENC-M3	3	1	10	32	51	60	220	6 X 1
PENC-D-M6	6	2	18	32	51	60	220	6 X 2
PENC-D-M9	9	3	28	32	51	60	220	6 X 3
PENC-D-M12	12	4	36	32	51	60	220	6 X 4
PENC-D-M18	18	6	54	32	51	60	220	6 X 6
PENC-M6	6	1	18	32	51	60	220	6 X 2
PENC-M9	9	1	28	32	51	60	220	6 X 3
PENC-M12	12	2	36	32	51	60	220	6 X 4
PENC-M18	18	2	54	32	51	60	220	6 X 6



ETL US

This item meets the electrical product safety standards imposed by the ETL, a division of the Intertek Group, for use in the United States.



ETL Sanitation

This item meets the sanitation standards imposed by the ETL, a division of the Intertek Group.

Product Dimensions

